



**POWER
STEERING
FLUID**

**GOLD
PREMIUM
AUTOMATIC
TRANSMISSION FLUID
ATF**

**AUTOMATIC
TRANSMISSION
FLUID**

DEXRON III FLUID [1 & 4 LITRES]

HELLO™ ATF DEXRON III consists of high quality paraffinic base oil and additive systems to provide excellent foam resistance, corrosion and wear protection. It is reinforced with specially selected friction modifiers to meet the demanding frictional requirements of the automatic transmission. Shelf life provided is 3 to 3½ years.

CARTON PACKING

- 24 X 1L & 6 x 4L

BENEFITS

- Ensures long servicing life.
- Provides high form stability.
- Superb anti-wear properties.
- Smoother & quieter automatic transmission
- Excellent frictional, oxidative and thermal stability.
- Provides anti rust protection and lower sludge formation.
- Provides good start operation in cold climates by low temperature fluidity.

PRODUCT PERFORMANCE CLAIM:

GM Dexron III, Dexron III E, Mercon Fluid, Allison C-4 Fluid, Caterpillar TO-2 Lubricant, MIL-L-2104 D

CERTIFICATE OF ANALYSIS (COA):

PARAMETERS	METHOD	UNIT	SPECIFICATION	RESULT
KINEMATIC VISCOSITY@100°C	ASTM D445	cSt	6.90 - 8.10	7.10
KINEMATIC VISCOSITY@40°C	ASTM D445	cSt	REPORT	40.30
VISCOSITY INDEX	ASTM D2770	-	-	139
SPECIFIC GRAVITY@15°C	ASTM D4052	kg/m3	0.86 - 0.90	0.86
FLASH POINT	ASTM D93	°C	MIN 210	213
COLOUR	ASTM D1500	-	0.5 - 3.0	3.0