



# GOLD PREMIUM AUTOMATIC TRANSMISSION FLUID ATF SP III FLUID [1 & 4 LITRES]

**AUTOMATIC  
TRANSMISSION  
FLUID**

**HELLO™ ATF DEXRON III** consists of high quality paraffinic base oil and additive systems to provide excellent foam resistance, corrosion and wear protection. It is reinforced with specially selected friction modifiers to meet the demanding frictional requirements of the automatic transmission. Shelf life provided is 3 to 3½ years.

## CARTON PACKING

- 24 X 1L & 6 x 4L

## BENEFITS

- Ensures long servicing life.
- Provides high form stability.
- Superb anti-wear properties.
- Smoother & quieter automatic transmission
- Excellent frictional, oxidative and thermal stability.
- Provides anti rust protection and lower sludge formation.
- Provides good start operation in cold climates by low temperature fluidity.

## PRODUCT PERFORMANCE CLAIM:

- **HITEC® 3418M(4011) MEET OR EXCEED THE PERFORMANCE :**  
Toyota T-III, IV and WS, Nissan Matic-D and J, Mitsubishi SP-II and SP-III, Hyundai / Kia SP-III, Honda, JASO M315 1A Japanese and Korean
- **US OEM REQUIREMENTS :**  
DEXRON® III, MERCON® performance levels)
- **EUROPEAN OEM REQUIREMENTS:**  
(ZF TE-ML-14A, Voith 55.6335, MAN 339 Type Z-1 and V-1, MB 236.1)

## CERTIFICATE OF ANALYSIS (COA):

| PARAMETERS                | METHOD     | UNIT  | SPECIFICATION | RESULT |
|---------------------------|------------|-------|---------------|--------|
| KINEMATIC VISCOSITY@100°C | ASTM D445  | cSt   | 6.90 - 8.10   | 7.3    |
| KINEMATIC VISCOSITY@40°C  | ASTM D445  | cSt   | REPORT        | 42.7   |
| VISCOSITY INDEX           | ASTM D2270 | -     | -             | 136    |
| SPECIFIC GRAVITY@15°C     | ASTM D4052 | kg/m3 | 0.86 - 0.90   | 0.86   |
| FLASH POINT (PMCC)        | ASTM D93   | °C    | MIN 210       | 217    |
| COLOUR                    | ASTM D1500 | -     | 0.5 - 3.0     | 3.0    |