



**GOLD
PREMIUM
DIESEL ENGINE OIL
SAE**

15W-40 API CI-4/SL [7 LITRES]



recommends
an **API CI-4**
specification.



**PREMIUM
DIESEL
ENGINE OIL**

HELLO™ PREMIUM DIESEL ENGINE OIL SAE 40 API CI-4/SL, today's technology trend of diesel engine is towards more environment conscious products with less gas emission and longer overhaul period. Coming along with these development, new devices like the Exhaust Gas Recirculation (EGR) rely much more on the performance of the engine oil being used. Premium Diesel Engine Oil SAE 15W-40, using only the hydro-treated base oil to maximize the protection under severe operating conditions, is well positioned to address those needs.

CARTON PACKING

- 4 x 7L

BENEFITS

- Minimizes oil consumption.
- Satisfying most diesel engine OEM oil demands.
- Hydro-treated base, inherent thermal-stability & anti-oxidation property.
- Particular suitable for the modern diesel engine equipped with EGR.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS:

- API CI-4/SL, ACEA A3/B4, E3/E5/E7, JASO DH-1
- Mercedes Benz 228.3 / 229.1, Mack EO-L/EO-M / EO-N, ZF TE-ML-04C, Caterpillar ECF-2, MTU Type-2, Renault Truck RLD/RLD-2, Alison C-4, Volvo VDS 3, Man 270 / 271 / M3275, Global DHD-1, Cummins 20071 / 20072 / 20076 / 20077 / 20078 / Detroit Diesel DDC 93K215, VW 505.

CERTIFICATE OF ANALYSIS (COA):

PARAMETERS	METHOD	UNIT	SPECIFICATION	RESULT
KINEMATIC VISCOSITY@100°C	ASTM D445	cSt	12.50 - 16.30	15.80
KINEMATIC VISCOSITY@40°C	ASTM D445	cSt	REPORT	132.80
VISCOSITY INDEX	ASTM D2770	-	-	125
SPECIFIC GRAVITY@15°C	ASTM D4052	kg/m3	0.86 - 0.90	0.88
FLASH POINT	ASTM D93	°C	MIN 210	213
COLOUR	ASTM D1500	-	0.5 - 3.0	2.5