



recommends
an **API SN** or
earlier specification.

**SYNTHETIC
FORMULATION
ENGINE OIL
SAE**



**SYNTHETIC
FORMULATION
ENGINE OIL**

10W-40 API SN [4 LITRES]

HELLO™ SYNTHETIC FORMULATION ENGINE OIL is a premium quality, semi-synthetic engine oil providing increased wear protection, better resistance to sludge formation and lower piston deposits. This oil is specially engineered to keep engine in peak performance.

CARTON PACKING

- 4 x 4L

BENEFITS

- Formulated with advance additives for engine wear protection to prolong engine life.
- Protection against viscosity and thermal breakdown.
- Keeps engines cool and clean to maintain performance.
- Helps minimize oil consumption.

APPLICATION

HELLO™ SYNTHETIC FORMULATION ENGINE OIL is suitable for use in petrol, LPG or CNG cars, light commercial vehicles and 4WDs where API SN or earlier specifications are recommended.

PRODUCT PERFORMANCE CLAIM:

API SN

CERTIFICATE OF ANALYSIS (COA):

PARAMETERS	METHOD	UNIT	SPECIFICATION	RESULT
DENSITY@15°C	ASTM D4052	kg/l	REPORT	0.8604
DENSITY@30°C	ASTM D4052	kg/l	REPORT	0.8509
FLASH POINT (PMCC)	ASTM D93	°C	MIN 190	230
COLOUR	ASTM D1500	-	REPORT	2.5
APPEARANCE	VISUAL	-	BRIGHT & CLEAR	BRIGHT & CLEAR
KINEMATIC VISCOSITY@40°C	ASTM D7042	mm ² /s	REPORT	98.06
KINEMATIC VISCOSITY@100°C	ASTM D7042	mm ² /s	13.50 - 15.50	14.3
VISCOSITY INDEX	ASTM D2270	-	MIN 135	150
TOTAL BASE NUMBER	ASTM D2896	mg KOH/g	MIN 6.00	6.56
ZINC	ASTM D4951	%wt	0.0640 - 0.1040	0.0831
PHOSPHORUS	ASTM D4951	%wt	0.0500 - 0.0800	0.0746
CALCIUM	ASTM D4951	%wt	0.1650 - 0.2050	0.1857
POUR POINT	ASTM D97	°C	MAX -30	-39
CCS@25°C	ASTM D5293	cP	MAX 7000	6130