



PREMIUM
ENGINE OIL

SAE
15W-40 API SN [4 LITRES]



recommends
an **API SN**
specification.



PREMIUM
ENGINE OIL

HELLO PREMIUM ENGINE OIL SAE 15W-40 API SN is a high performance engine lubricant, designed to meet the requirements of a wide range of naturally aspirated and turbo charged petrol engines.

CARTON PACKING

- 4 x 4L

BENEFITS

- Keeps engine clean to main peak performance.
- Excellent protection against wear to prolong engine life.
- Protects engine in high performance and high temperature operation.
- Very high resistance against oxidation to prolong oil change interval.

APPLICATION

HELLO PREMIUM ENGINE OIL SAE 15W-40 API SN is recommended for use in all types of passenger cars and latest model high performance cars fitted with fuel injections, multi-valves, turbochargers or superchargers operating under the most extreme conditions. Also suitable for engines requiring API SL, SJ, SH, SG or lower performance levels.

PRODUCT PERFORMANCE CLAIM:

API SN

CERTIFICATE OF ANALYSIS (COA):

PARAMETERS	METHOD	UNIT	SPECIFICATION	RESULT
DENSITY@15°C	ASTM D4052	kg/l	REPORT	0.8728
DENSITY@30°C	ASTM D4052	kg/l	REPORT	0.8633
FLASH POINT (PMCC)	ASTM D93	°C	MIN 190	230
COLOUR	ASTM D1500	-	REPORT	2.5
APPEARANCE	VISUAL	-	BRIGHT & CLEAR	BRIGHT & CLEAR
KINEMATIC VISCOSITY@40°C	ASTM D7042	mm²/s	REPORT	115.13
KINEMATIC VISCOSITY@100°C	ASTM D7042	mm²/s	14.0 - 15.60	14.74
VISCOSITY INDEX	ASTM D2270	-	MIN 120	131.5
TOTAL BASE NUMBER	ASTM D2896	mg KOH/g	MIN 5.0	6.05
CALCIUM	ASTM D4951	%wt	0.1650 - 0.2050	0.1766
ZINC	ASTM D4951	%wt	0.0640 - 0.1040	0.0806
PHOSPHORUS	ASTM D4951	%wt	0.0500 - 0.0800	0.0714
POUR POINT	ASTM D97	°C	MAX -25	-28
CCS@-20°C	ASTM D5293	cP	MAX 7000	6553