



**FULLY
SYNTHETIC**
ENGINE OIL
SAE

5W-40 API SN [4 LITRES]



recommends
an **API SN** or
earlier specification.



**FULLY
SYNTHETIC**
ENGINE OIL

HELLO™ FULLY SYNTHETIC ENGINE OIL SAE 5W-40 API SN is high performance fully synthetic multi grade engine oil. This oil is developed with high-quality synthetic base oils and latest additive technology and is recommended as an all-season engine oil in high performance engines including turbo charged.

CARTON PACKING

- 4 x 4L

BENEFITS

- Excellent cold weather start.
- Keeps engine clean to maintain peak performance.
- Prolong oil drain interval.
- Reliable protection against wear and corrosion in severe conditions to prolong engine life.

APPLICATION

HELLO™ FULLY SYNTHETIC ENGINE OIL SAE 5W-40 API SN is suitable for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline and certain diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks where the manufacturer recommends an API SN or earlier specification.

PRODUCT PERFORMANCE CLAIM:

API SN

CERTIFICATE OF ANALYSIS (COA):

PARAMETERS	METHOD	UNIT	SPECIFICATION	RESULT
APPEARANCE	VISUAL	-	BRIGHT & CLEAR	BRIGHT & CLEAR
COLOUR	ASTM D1500	-	REPORT	2.5
DENSITY@15°C	ASTM D4052	kg/l	REPORT	0.8548
DENSITY@30°C	ASTM D4052	kg/l	REPORT	0.8454
FLASH POINT (PMCC)	ASTM D93	°C	MIN 190	220
KINEMATIC VISCOSITY@40°C	ASTM D7042	mm ² /s	REPORT	85.05
KINEMATIC VISCOSITY@100°C	ASTM D7042	mm ² /s	13.5 - 15.5	13.9
VISCOSITY INDEX	ASTM D2270	-	MIN 160	168
TOTAL BASE NUMBER	ASTM D2896	mg KOH/g	MIN 6.00	6.63
CALCIUM	ASTM D4951	%wt	0.1650 - 0.2050	0.1964
ZINC	ASTM D4951	%wt	0.0640 - 0.1040	0.0870
PHOSPHORUS	ASTM D4951	%wt	0.0500 - 0.0800	0.0777
POUR POINT	ASTM D97	°C	MAX -35	-41
CCS@30°C	ASTM D5293	cP	MAX 6600	6327