



REDUCES
DIRTY SLUDGE
& WEAR DEPOSITS
FORMATION

GOLD
PREMIUM
AUTO MAINTAINANCE
100%

INCREASES
OIL
CHANGE

ENGINE TREATMENT [236 ML]

HELLO™ ENGINE TREATMENT is exclusively formulated to blend with petroleum and synthetic oils, gear lubes, transmission fluids and grease. It contains no solids to retard penetration and will not cause any material build up or change even the finest of machine tolerances. Used in conjunction with **HELLO™ ENGINE TREATMENT** and other **HELLO™** fine products, your vehicle engine will perform at peak levels while generating the benefits of fuel savings to you.

CARTON PACKING

- 24 x 236ML

BENEFITS

- Protection from wear between 4 to 5 times as compared to normal lubricants.
- Improves fuel mileage.
- Reduces dirty sludge, hard varnish & wear deposits formation.
- Prolongs the life of the engine, transmission, gear box and differential.
- Protects the moving metal parts against heat and friction.
- Increases acceleration, horsepower, torque and performance.
- Penetrates the metal surface to form a polished shield (low friction shield) that reduces friction
- Engine and engine components is cooler, cleaner, smoother and quieter.
- Increases oil change period by at least 50%.

CERTIFICATE OF ANALYSIS (COA):

PARAMETERS	METHOD	UNIT	SPECIFICATION	RESULT
KINEMATIC VISCOSITY@100°C	ASTM D445	cSt	6.50 - 9.00	7.80
KINEMATIC VISCOSITY@40°C	ASTM D445	cSt	REPORT	48.50
VISCOSITY INDEX	ASTM D2770	-	-	129
SPECIFIC GRAVITY@15°C	ASTM D4052	kg/m ³	1.00 - 1.20	1.1167
FRICION LUBRICITY TEST, FOOT PONDS	FALEX FRICTION & WEAR TEST	-	2 FOOT - 12 FOOT POUNDS POUNDS	12 FOOT PONDS
COLOUR	ASTM D1500	-	0.5 - 3.0	2.5
APPEARANCE	VISUAL	-		BRIGHT & CLEAR