



GOLD
PREMIUM
GEAR OIL

MANUAL
TRANSMISSION
FLUID

SAE 80W-90 API GL-5 [4 LITRES]

HELLO™ SAE 80W/90 GL5 is a multi-grade automotive gear lubricants with extreme pressure additive and consisting of premium synthetic base oils. It is reinforced with friction modifiers and other additives to produce an extra ordinary gear lubricant. It is a high grade premium gear lubricant manufactured from selected highly refined base oil. Specially made for use in automotive gears, particularly hypoid gear units, heavy duty industrial type enclosed gear units, steering gears and fluid lubricated universal joints of automotive equipment where limited slip properties are required. It is highly recommended for a wide range of temperature operation between -35 oC to 180 oC. Recommended shelf life is 3 to 3½ years.

CARTON PACKING

- 6 x 4L

BENEFITS

- Excellent performance at low temperature.service conditions.
- Excellent protection against extreme pressure.
- Superior protection against wearing and scoring produced by high speed, low speed and heavy loads.
- Recommended for a wide variety of applications and service conditions.
- Reduces cost by increasing the life span of the gear lubricants.
- Superior sulfur & phosphorus additives.
- Superior protection against corrosion, rusting & staining and corrosion.

PRODUCT PERFORMANCE CLAIM:

SAE 80W/90 API GL -5, MIL -L-2105

CERTIFICATE OF ANALYSIS (COA):

PARAMETERS	METHOD	UNIT	SPECIFICATION	RESULT
KINEMATIC VISCOSITY@100°C	ASTM D445	cSt	13.50 - 8.10	14.70
KINEMATIC VISCOSITY@40°C	ASTM D445	cSt	REPORT	139.5
VISCOSITY INDEX	ASTM D2770	-	-	105
SPECIFIC GRAVITY@15°C	ASTM D4052	kg/m3	0.86 - 0.90	0.878
FLASH POINT	ASTM D93	°C	MIN 210	225
COLOUR	ASTM D1500	-	0.5 - 3.0	2.5